IN THE CLAIMS:

1. (Currently Amended) A <u>self-supporting</u> polysiloxane film comprising a polysiloxane <u>obtainedcrosslinked</u> by <u>erosslinkingreacting</u>, in the presence of a platinum catalyst, a polysiloxane having an unsaturated aliphatic hydrocarbon group in one molecule and represented by the average structural formula: (1) $R^1_aSiO_{(4-a)/2}$ (where R^1 is a $C_1\sim C_{10}$ monovalent hydrocarbon group and the subscript «a» is a positive number in the range of 0<a<2) with an organosilicon compound having, in each molecule, at least two hydrogen atoms directly bonded to silicon atoms.

2. (Currently Amended) The <u>self-supporting</u> polysiloxane film according to Claim 1, in which the polysiloxane represented by the above-mentioned average structural formula (1) comprises $(XR^2_2SiO_{1/2})$ units (where X is a $C_2\sim C_{10}$ monovalent unsaturated aliphatic hydrocarbon group, and R^2 is a $C_1\sim C_{10}$ monovalent hydrocarbon group other than X) and $(R^3SiO_{3/2})$ units (where R^3 is a $C_1\sim C_{10}$ monovalent hydrocarbon group other than X) as essential constitutional units.

3. (Currently Amended) The <u>self-supporting</u> polysiloxane film according to Claim 1, in which the polysiloxane represented by the above-mentioned average structural formula (1) comprises ($R_n^4 SiO_{(4-n)/2}$) units (where R^4 is selected independently from a $C_1 \sim C_{10}$ monovalent hydrocarbon group and a $C_2 \sim C_{10}$ monovalent unsaturated aliphatic hydrocarbon group, and «n» is 1, 2, or 3)[[,]] and (SiO_{4/2}) units, and contains an unsaturated aliphatic hydrocarbon group-in-one-molecule.

4. (Currently Amended) The <u>self-supporting</u> polysiloxane film according to Claim 1 which does not have a specific light absorption band in the visible wavelength range and has an optical transmissivity of not less than 85% at 400 nm and an optical transmissivity of not less than 88% in the wavelength range of from 500 nm to 700 nm.

5. (Cancelled)

6. (Currently Amended) A method of manufacturing a <u>self-supporting</u> polysiloxane film comprising the steps of:

forming an uncured film by coating a substrate with a crosslinkable polysiloxane composition comprising a polysiloxane having an unsaturated aliphatic hydrocarbon group—in one molecule and represented by the average structural formula: (1) $R^1_a SiO_{(4-a)/2}$ (where R^1 is a $C_1 \sim C_{10}$ monovalent hydrocarbon group and the subscript «a» is a positive number in the range of 0 < a < 2), an organosilicon compound having, in each molecule, at least two hydrogen atoms directly bonded to silicon atoms, and a platinum catalyst;

producing a cured film by crosslinking the above-mentioned uncured film; and peeling off the above-mentioned cured film from the above-mentioned substrate.

7. (Currently Amended) The method of manufacturing a <u>self-supporting</u> polysiloxane film according to Claim 6, wherein the polysiloxane represented by the above-mentioned average structural formula (1) comprises $(XR^2_2SiO_{1/2})$ units (where X is a $C_2\sim C_{10}$ monovalent unsaturated aliphatic hydrocarbon group and R^2 is independently a $C_1\sim C_{10}$ monovalent hydrocarbon group other than X) and $(R^3SiO_{3/2})$ units (where R^3 is a $C_1\sim C_{10}$ monovalent hydrocarbon group other than X).

- 3 -

- 8. (Currently Amended) The method of manufacturing a <u>self-supporting</u> polysiloxane film according to Claim 6, wherein the polysiloxane represented by the above-mentioned average structural formula (1) comprises ($R^4_n SiO_{(4-n)/2}$) units (where R^4 is selected independently from a $C_1 \sim C_{10}$ monovalent hydrocarbon group and a $C_2 \sim C_{10}$ monovalent unsaturated aliphatic hydrocarbon group, the subscript «n» is 1, 2, or 3)[[,]] and (SiO_{4/2}) units, and contains in one molecule an unsaturated aliphatic hydrocarbon group.
- 9. (Original) A laminated film comprising an inorganic substance layer on a transparent substrate made from a self-supporting cross-linked polysiloxane that does not have a specific light absorption band in the wavelength range of 400 nm to 800 nm.
- 10. (Original) The laminated film of Claim 9, wherein said inorganic substance layer is a layer of metal or a semiconductor metal oxide applied by vapor deposition.
- 11. (Currently Amended) The laminated film according to Claim 9, wherein said crosslinked polysiloxane film is made from a polysiloxane obtained crosslinked by erosslinking a polysiloxane that contains containing an unsaturated aliphatic hydrocarbon group in one molecule and [[is]] represented by the following average structural unit formula (1):

$$R^{1}_{a}SiO_{(4-a)/2}$$
 (1)

(where R^1 is a $C_1\sim C_{10}$ monovalent hydrocarbon group and the subscript «a» is a positive number in the range of 0<a<2) and an organosilicon compound having, in each molecule, at least two hydrogen atoms directly bonded to silicon atoms, said crosslinking being carried out in the presence of a platinum catalyst.

12. (Original) The laminated film according to Claim 11, wherein said polysiloxane represented by the above-mentioned average structural formula (1) comprises $(XR^2_2SiO_{1/2})$ units (where X is a $C_2\sim C_{10}$ monovalent unsaturated aliphatic hydrocarbon group and R^2 is a $C_1\sim C_{10}$ monovalent hydrocarbon group other than X) and $(R^3SiO_{3/2})$ units (where R^3 is a $C_1\sim C_{10}$ monovalent hydrocarbon group other than X).

13. (Currently Amended) The laminated film according to Claim 11, wherein said polysiloxane represented by the above-mentioned average structural formula (1) comprises $(R^4_nSiO_{(4-n)/2})$ units (where R^4 is selected independently from a $C_1\sim C_{10}$ monovalent hydrocarbon group and a $C_2\sim C_{10}$ unsaturated aliphatic hydrocarbon group, the subscript «n» is 1, 2, or 3)[[,]] and $(SiO_{4/2})$ units, and contains an unsaturated aliphatic hydrocarbon group in one molecule.

14. (Original) A method of manufacturing a laminated film by forming an inorganic substance layer in a vacuum film-forming process at a temperature not exceeding 300°C on a transparent substrate made from a self-supporting cross-linked polysiloxane that does not have a specific light absorption band in the wavelength range of 400 nm to 800 nm.

- 5 -

02